

EZReball™ Backing Material

Safety Data Sheet



EZReball™ Backing Material

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

Product Name: EZReball™ Backing Material
Synonyms: Tape
Distributor: BEST Inc
3603 Edison Place
Rolling Meadows IL
(897) 797 9250



GHS Signal Word: Warning

SECTION 2: HAZARDS IDENTIFICATION

Routes of Entry: Inhalation, Ingestion, Skin/Eye Contact

Potential Health Effects

Eye Contact: Unlikely route of exposure.

Inhalation: Unlikely route of exposure.

Skin Contact: No irritation is expected from handling film. Less than 1 ppm dim ethyl acetamide was extracted from film by distilled water at 40°C for 4 hours

Ingestion: Unlikely route of exposure.

MEDICAL CONDITIONS POSSIBLY AGGRAVATED BY EXPOSURE:

Diseases of the blood-forming organs, kidneys, nervous and possibly reproductive systems

POTENTIAL HEALTH EFFECTS

EYE CONTACT: Rinse with warm water and gently peel. Flush eyes with water. Contact a physician if irritation persists.

INHALATION: Unlikely route of exposure.

SKIN CONTACT: No irritation is expected from handling tape.

INGESTION: Unlikely route of exposure.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Material:

- Cloth
- Silicone Adhesive

SECTION 4: First aid measures

Inhalation: Not a probable route of exposure for tape.

12/12/2018

SDS Ref.: EZ Backing Material

1/5

EZReball™ Backing Material

Safety Data Sheet

Eye Contact: Not a probable route of exposure for tape.
Skin Contact: Contact a physician if frequent irritation is experienced after use.
Ingestion: Not a probable route of exposure for tape.

SECTION 5: FIREFIGHTING MEASURES

Flammable Properties: P-212 WHT is a high thermal rating tape along with solvent resistance and flame retardancy.
Extinguishing Media: N/A
Fire Fighting Instructions: None required

SECTION 6: ACCIDENTAL RELEASE MEASURES

Accidental Release Measures: Pick up to prevent slipping hazard.

SECTION 7: HANDLING AND STORAGE

Handling (Personnel): N/A
Storage: Store away from flammable materials. Best stored between 50-80 degrees Fahrenheit (10-27 degrees Celsius), away from direct sunlight, and with a relative humidity of 25-50%.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

ENGINEERING CONTROLS:

- N/A

Personal Protective Equipment

- N/A

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Backing Material: Cloth
Adhesive: Cured Plastic
Total Tape Thickness: 7.5 mil / 0.191mm
Tensile Strength: 185 lbs/in. // 323 N/10mm
Elongation: 8.8% / 8.8%
Color: White
Adhesion to Steel: 59 oz/in // 6.5N/10mm
Dielectric Strength: 4,400 Volts / 4.4kV
Insulation Class CSA: 356 degrees Fahrenheit / 180 degrees Celsius
Insulation Class LU: 392 degrees Fahrenheit / 200 degrees Celsius
Chemical Data: N/A

SECTION 10: STABILITY AND REACTIVITY

General: N/A
Incompatible materials and Conditions to Avoid: N/A
Hazardous Decomposition or Byproducts: N/A

SECTION 11: TOXICOLOGICAL INFORMATION

Carcinogenicity: N/A

SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicological Information

- **Aquatic Toxicity** N/A

SECTION 13: DISPOSAL CONSIDERATIONS

Waste Disposal Method: N/A

SECTION 14: TRANSPORT INFORMATION

EZReball™ Backing Material

Safety Data Sheet

SHIPPING INFORMATION

DOT Not Regulated

SECTION 15: REGULATORY INFORMATION

- N/A

SECTION 16: OTHER INFORMATION

RESPONSIBILITY FOR SDS: Best, Inc.

KEY:

N/A: Not Applicable
GHS: Global Harmonized System

To the best of our knowledge, the information contained herein is accurate. However, neither Best Inc., nor any of its distributors assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist.