Epoxy-Resin



SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

Product Name: Epoxy Resin

Distributor: BEST Inc

3603 Edison Place Rolling Meadows IL (897) 797 9250



GHS Signal Word: Warning

SECTION 2: HAZARDS IDENTIFICATION

Routes of Entry: Inhalation, Ingestion, Skin/Eye Contact

DANGER: CUASES SEVER BURNS AND EYE DAMAGE. MAY CAUSE AN ALLERGIC SKIN REACTION.

Potential Health Effects

Serious Eye Damage: 1.
Skin Corrosion: 1B
Skin Sensitization: 1

<u>Prevention</u>: Do not breath dust of fumes. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Wear protective clothes, gloves, eye protection and face protection.

<u>Response</u>: IF SWALLOWED rinse mouth. Do not induce vomiting. If on skin or hair take off immediately all contaminated clothing. If inhaled remove person to fresh air and keep comfortable for breathing.

Storage: Store locked up

<u>Disposal</u>: Dispose of contents and or container according to federal, state and local governmental laws.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

 Hazardous Components
 CAS Number
 Percentage

 Polyamide
 Proprietary
 60 – 100

 Triethylenetetramine
 112-4-3
 10-30

 Silica,amorphous,fumed, crystal-free
 112945-52-5
 1-5

Trade secrets on exacting percentages

1/25/2019 SDS Ref.: Epoxy Resin 1/5

SECTION 4: First aid measures

Inhalation: Move to fresh air. Get medical attention if necessary

Eye Contact: Flush eyes with water. Get a physician consultation if an irritation persists.

Skin Contact: Wash with soap and water after handling. If skin irritation develops, consult a physician.

Ingestion: DO NOT induce vomiting unless directed to do so by medical personnel. Get medical attention immediately.

SECTION 5: FIREFIGHTING MEASURES

Flammable Properties: Not a fire or explosion hazard

Extinguishing Media: Water, Foam, Dry Chemical, CO₂

Unusual Fire Hazards: In case of fire keep containers cools with water spray. Closed containers may rupture (due to

pressure build up) when exposed to extreme heat

Special Firefighting instructions: Wear self-contained breathing apparatus nd full protective clothing.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Safeguards (Personnel) NOTE: Review FIRE FIGHTING MEASURES and HANDLING (PERSONNEL) Sections before proceeding with

clean up. Use appropriate PERSONAL PROTECTIE EQUIPMENT during clean up.

Accidental Release

Do not allow product to enter sewer or waterways

Measures:

SECTION 7: HANDLING AND STORAGE

Handling Use only with adequate ventilation. Prevent contact with eyes, skin and clothing. Do not breath vapor and mist. Wash

thoroughly after handling. Keep container closed.

Storage: Store in original container until ready to use. Keep container tightly closed and in a cool, well-ventilated place away from

incompatible materials.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

ENGINEERING CONTROLS:

- Provide adequate local exhaust ventilation to maintain worker exposure below exposure limits..

Respiratory Protection: Use a NIOSH approved air-purifying respirator if the potential to exceed established exposure limits

Skin Protection: Use chemical resistant, impermeable clothing including gloves and either an apron or body suit to prevent

skin contact..

Eye/Face Protection: Safety glasses are recommended as good industrial practice.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Odor: Ammoniacal
Melting Point: Not available
Appearance: Dark amber to Black
Solubility in Water: Not miscible or difficult to mix

% Volatiles 1% Max Specific Gravity >0.98

SECTION 10: STABILITY AND REACTIVITY

Stability: Stable under normal conditions of storage and use.

Hazardous Reactions: Polymerization is a highly exothermic reaction and may generate sufficient heat to cause

thermal decomposition and or ruptured containers.

Hazardous Decomposition Products: Hydrocarbons. Oxides of Carbon. Oxides of Nitrogen. Irritating organic vapors.

Incompatible Materials: Stable at normal temperatures and storage conditions.

Reactivity:

Conditions to Avoid Avoid Avoid temperatures above 38C (100F). Excessive heat, flames, sparks and other sources

of ignition. Store away from incompatible materials. Avoid mixing resin ({Part A) and curing agent Part B) unless you plan to use immediately. Failure to observe these

precautions may result in excessive heat.

1/25/2019 SDS Ref.: Epoxy Resin 2/5

SECTION 11: TOXICOLOGICAL INFORMATION

Relevant routes of exposure: Skin, inhalation, eyes, ingestion.

Inhalation: May cause irritation to nose and throat. Inhalation of vapors or mists of the product may be irritating to the respiratory system.

Skin Contact: Corrosive to skin. Causes skin burns. May cause allergic skin reaction. Rash. Redness.

Eye Contact: Causes serious eye damage. Redness. Tissue damage.

Ingestion: May cause burns of the mouth and throat if swallowed. Irritation and corrosive action can occur in the mouth stomach tissue and

digestive tract if swallowed.

SECTION 12: ECOLOGICAL INFORMATION

Ecological Information: Not available.

SECTION 13: DISPOSAL CONSIDERATIONS

Waste Disposal Method: Landfill or incinerate in compliance with federal, state and local regulations.

SECTION 14: TRANSPORT INFORMATION

SHIPPING INFORMATION

DOT Haz class: 8 ID Number: UN 2259 Packing Group II

International Air Transportation Haz class: 8 ID Number: UN 2259 Packing Group II

SECTION 15: REGULATORY INFORMATION

US States Regulatory Information

- TSCA 8 (b) Inventory Status: All components are listed or are exempt from listing on the Toxic Substances Control Act inventory.
- TSCA 12 (b) Notification: None above reporting de minimus
- o CERCLA/SARA Section 302 EHS: 12 : None above reporting de minimus
- o CERCLA/SARA Section 311/312 EHS: 12 : Immediate Health, Delayed Health
- o CERCLA/SARA Section 313 EHS: 12 : None above reporting de minimus

California Proposition 65: No CA Prop 65 listed chemicals are known to be present

SECTION 16: OTHER INFORMATION

MEDICAL USE: Do not use in medical applications involving permanent implantation in the human body. The data in this Safety Data Sheet relate only to the specific material designated herein and does not relate to use in combination with any other material or in any process.

RESPONSIBILITY FOR SDS: Best, Inc.

KEY:

N/A: Not Applicable

GHS: Global Harmonized System

OSHA: Occupational Safety and Health Administration

PEL: Permissible Exposure Limit

ACGIH: American Conference of Governmental Industrial Hygienists

TLV: Threshold limit value
NTP: National Toxicology Program

IARC: International Agency for Research on Cancer

DOT: Department of Transportation TSCA: Toxic Substance Control Act

To the best of our knowledge, the information contained herein is accurate. However, neither Best Inc., nor any of its distributors assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist.

1/25/2019 SDS Ref.: Epoxy Resin 3/5

1/25/2019 SDS Ref.: Epoxy Resin 4/5